



# PROPULSION MOTOR DISMANTLING

3381 NW 168 Street  
Miami Gardens, FL 33056  
USA

TEL: +1 305 592 3473  
[INFO@RCG-USA.COM](mailto:INFO@RCG-USA.COM)  
[SPARES@RCG-USA.COM](mailto:SPARES@RCG-USA.COM)

# TABLE OF CONTENT

## 1- Study

1.1 Feasibility analysis

1.2 Architectural calculations for ship structural modifications

1.3 Structure design and calculations

1.4 Preparation: Planning, processes, tooling and manning

## 2- Work performed

2.1 Preparation inside the ship

2.2 Lifting of motor

2.3 Structure construction

2.4 Removal of motor


2.5 Dismantling of rotor in shipyard

2.6 Reinstallation of motor

Project during Covid  
Logistic  
Weather control


# 1.2-Architectural calculations for ship structural modifications

## Reinforcement of hull for opening




# 1.2-Architectural calculations for ship structural modifications

## Reinforcement of deck for pillar removal



# 1.3-Structure design and calculations

Calculation of all skidding system used with different case scenarios



The profile chosen for this beam is W10 x 10 x 112, with an elastic section modulus  $W_z = 2078 \text{ cm}^3$

We are going to study the worst-case scenario, when the spacing of the legs under the structure is 2000mm, and the weight of the motor is right in the middle.

With motor weight 128Tons, each of the 4 supports will take 32 tons  $\approx 320 \text{ N}$

We consider only the beam in the calculation and none of the stiffeners and reinforcement that will be welded to it.

Mode of failure due to bending - Bending stress:



$$\sigma_x = \frac{M_z \cdot y}{I_z} = \frac{M_z}{W_z}$$


where

- $\sigma_x$  is the bending stress
- $M_z$  - the moment about the neutral axis
- $y$  - the perpendicular distance to the neutral axis
- $I_z$  - the second moment of area about the neutral axis z.
- $W_z$  - the Resistance Moment about the neutral axis z.  $W_z = I_z/y$

In our case,  $M_z = \frac{PL}{4} = \frac{320000 \times 2}{4} = 160\,000 \text{ Nm}$


$$\sigma_x = \frac{M_z}{W_z} = \frac{160000000}{2078000} = 77 \text{ Mpa}$$

The yield strength for normal strength steel ASTM A36 is 250 MPa which is much higher than the load on the beam.




# 1.4 -Preparations

## Planning




Tooling, controlled and certified






## 2.1- Preparation inside ship



Various type of element to be dism  
Availability of technicians specialize  
Electricians, pipe fitters, welders, rig



## 2.1- Preparation inside ship





Displacement of power cables, converter disconnections, deck penetration removal







## 2.1- Preparation inside ship

Pipes removal  
Untightning





## 2.2- Lifting of motor







## 2.3- Structure construction




## 2.4- Removal of motor





## 2.5- Exchange of stator in shipyard





## 2.5- Exchange of stator in shipyard



